

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## **IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

F-058



(19)

JAPANESE PATENT OFFICE

## PATENT ABSTRACTS OF JAPAN

(11) Publication number: 01027251 A

(43) Date of publication of application: 30 . 01 . 88

(51) Int. Cl.

H01L 23/66  
H01G 1/035  
H01L 23/32

(21) Application number: 62183888

(22) Date of filing: 22 . 07 . 87

(71) Applicant: NEC IC MICROCOMPUT SYST LTD

(72) Inventor: SUDA KOJI

(54) SEMICONDUCTOR DEVICE

COPYRIGHT: (C)1989,JPO&amp;Japlo

(57) Abstract:

**PURPOSE:** To reduce inductance, and to prevent the malfunction of a semiconductor device being generated by inductance by directly connecting a capacitor to outer leads for a power supply and a GND in the semiconductor device.

**CONSTITUTION:** A semiconductor chip 1 with pads 4A, 4B for a GND and a power supply is fixed onto a package 2, to which outer leads 3 including outer leads 3A, 3B for the GND and the power supply are formed and which consists of ceramics, etc. The pads 4A, 4B for the GND and the power supply are connected respectively to the outer leads 3A, 3B for the GND and the power supply by bonding wires 6A, 6B. A capacitor 5 is fastened onto the outer leads 3A, 3B, and a terminal 7A for the GND and a terminal 7B for the power supply for the capacitor 5 are directly connected respectively to the outer lead 3A for the GND and the outer lead 3B for the power supply. Accordingly, inductance is lowered, noises are reduced, and the generation of a malfunction can be prevented.

